





**SERIES CEE**  
**SOCKET OUTLET**  
**CODE 471103**



### Datasheet

#### Electrical characteristics

|                          |             |
|--------------------------|-------------|
| Rated current            | 16A         |
| Supply Voltage           | 42V 50/60Hz |
| Poles                    | 2P          |
| Clock Position           | 12h         |
| Rated insulation voltage | 500 V       |
| Signal plug inserted     | -           |

#### Reference Standards and Directives

|                                  |                                                                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification and approval marks | CB IMQ, UKCA, CE, IMQ                                                                                                                                                              |
| Directives                       | 2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR)                                                                                                                      |
| Reference Standards              | EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN IEC 63000:2018 |

#### Mechanical characteristics

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| Manufacturing material         | High resistance technopolymer                   |
| Alveolus/plugs treatment       | -                                               |
| Color                          | Grey RAL 7042                                   |
| Tightening diameter            | -                                               |
| Execution                      | Panel mounting                                  |
| IP Protection degree           | IP67                                            |
| Additional IPdegree protection | -                                               |
| Shock resistance               | IK08 according to IEC/EN 62262                  |
| Resistance to Glow wire        | 850°C                                           |
| Flame rating according UL94    | V-2                                             |
| Terminals type                 | Screw - direct tightening                       |
| Conductors section (Cu)        | Min: 4 mm <sup>2</sup> ;Max: 10 mm <sup>2</sup> |
| Terminal tightening torque     | 1,2 Nm                                          |
| Net Weight                     | 0.2 KG                                          |
| Working Environment Temp.      | Min: -25°C ;Max: +50°C                          |
| Warehousing Temperature        | Min: -30°C ;Max: +70°C                          |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.