



**SERIES MULTIMAX
PLUG**
CODE 710246



Connetti marchi (A)	N° Pol	A mm	Ø mm
16	3P+N+T	150	49,5
	3P+N+T	140	77,5
	3P+N+T	150	85,5
	3P+N+T	160	92,5
32	3P+N+T	160	92,5
	3P+N+T	185	92,5
	3P+N+T	170	98,5
	3P+N+T	250	111
63	3P+N+T	250	111
	3P+N+T	250	111
	3P+N+T	250	111
	3P+N+T	250	111



Datasheet

Electrical characteristics

Rated current	32A
Supply Voltage	400V 50/60Hz ●
Poles	3P+N+ $\frac{1}{2}$
Clock Position	6h
Rated insulation voltage	690 V
Signal plug inserted	-

Reference Standards and Directives

Certification and approval marks	UKCA, NYCE COLOMBIA, CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)
Reference Standards	EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN IEC 63000:2018

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Alveolus/plugs treatment	Nickel plated
Color	Grey RAL 7042
Tightening diameter	14÷21,5 mm
Execution	Mobile
IP Protection degree	IP67
Additional IPdegree protection	-
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	850°C
Flame rating according UL94	V-2
Terminals type	Screw - direct tightening
Conductors section (Cu)	Min: 2.5 mm ² ;Max:
Terminal tightening torque	1,8 Nm
Net Weight	0.29 KG
Working Environment Temp.	Min: -25°C ;Max: +50°C
Warehousing Temperature	Min: -30°C ;Max: +70°C

The images are purely indicative. Palazzoli reserves the right to make changes without notice.