

SERIES MULTIPLAY
ACCESSORY

CODE 740001



Datasheet

Specifications

Net Weight	0.17 KG
Rated current	16A
Frequency	50/60Hz
IP Protection degree	IPX0
Poles	2P+ $\perp$
Clock Position	6h
Rated operating voltage	230V ●
Rated insulation voltage	690 V V
Manufacturing material	Technopolymer Recyclable Palazzoli
Execution	Mobile
No. of power outgoing	1

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/35/EU (LVD)

Reference Standards CEI 23-50/V1:2008, CEI 23-50/V2:2011, CEI 23-50/V3:2015, CEI 23-50/V4:2015, CEI 23-50:2007, EN 50250:2002, EN 50250:2002/A1:2015, EN 50250:2002/AC:2007, EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.