

SERIES ENERGY BOX ACCESSORY

CODE 501595



Datasheet

Specifications

Net Weight	1.14 KG
Max conductor section	25 mm²
Storage room temperature MIN	-50°C
Min conductor section	6 mm²
Tightening diameter	14 ÷ 36 mm
Terminals type	Screw - indirect clamping
Shock resistance	IK10 according to IEC/EN 62262
Signal plug inserted	1 contact pilot
Terminal tightening torque	3 Nm
Alveolus/plugs treatment	Nickel plated
Storage room temperature MAX	+90°C
Max. Amb. Temp.	+60°C
Min. Amb. Temp.	-40°C
Rated insulation voltage	1000 V V
Rated current	63A
IP Protection degree	IP66/IP67
Frequency	50/60Hz
Poles	3P+N+ 
Additional IPdegree protection	IP68/IP69 - IEC 60529
Manufacturing material	Technopolymer Recyclable Palazzoli
Clock Position	6h
Characteristics	Wall-mounted industrial 63A 5P 400V inlet
Rated operating voltage	400V 
Standard plug-socket	IEC 60309-2

Reference Standards and Directives

Certification and approval marks -

Directives Reg. EU 2023/988 (GPSR)

Reference Standards

The images are purely indicative. Palazzoli reserves the right to make changes without notice.