




SERIES CAM-ST
TWO-WAY SWITCH
CODE 236252



Datasheet

Electrical characteristics

Rated current	25A
Supply Voltage	50V-500V~ 50/60Hz
Poles	2P
Rated insulation voltage	690 V
Insulation Class	-
CAM layout	9
Function Apparatus Control	Two way switches
Type of protection	None

Mechanical characteristics

Manufacturing material	High resistance technopolymer
Treatment type	-
Surface finishing	-
Color	-
Execution	Blackplane
Dimensions	48X48X76 mm
Depth	46
Front-plate dimension	48x48
Hole type	-
IP Protection degree	IP20
Additional IPdegree protection	IP65 front plate
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	0.14 KG
Working Environment Temp.	Min: -25°C ;Max: +60°C
Warehousing Temperature	Min: -40°C ;Max: +80°C

Technical data switch

Thermal current	25 A
Rated short-circuit current	10 kA
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 1.5 mm ² ;Max: 6 mm ²
Terminal tightening torque	1 Nm
Auxiliary status contacts	-
Padlockable handle	-

Operating category

Categoria Rating	Tensione Voltage	Corrente / Potenza Current / Power
AC-22A	230 V	25 A
	400 V	25 A
	500 V	25 A
AC-23A	690 V	25 A
	230 V	20 A
	400 V	20 A
AC-23A	500 V	16 A
	600 V	16 A
AC-3	230 V	6.4 kW
	400 V	11.1 kW
	500 V	11.1 kW
AC-3	600 V	13.3 kW
	230 V	5.7 kW
	400 V	10.0 kW
	500 V	11.1 kW
	600 V	15.3 kW

Reference Standards and Directives

Certification and approval marks	UKCA, CB IMQ, CE, IMQ, RINA_ELE094821CS
Directives	2014/35/EU (LVD)
Reference Standards	EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-1:2007/A2:2014, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN 60947-3:2009/A2:2015

The images are purely indicative. Palazzoli reserves the right to make changes without notice.