



**SERIES domoTER  
REVERSING SWITCH**  
**CODE 630031**



### Datasheet

#### Electrical characteristics

|                            |                    |
|----------------------------|--------------------|
| Rated current              | 16A                |
| Supply Voltage             | 250V 50/60Hz       |
| Poles                      | 1P                 |
| Rated insulation voltage   | -                  |
| Insulation Class           | II                 |
| CAM layout                 | -                  |
| Function Apparatus Control | Reversing switches |
| Type of protection         | -                  |

#### Mechanical characteristics

|                                |                               |
|--------------------------------|-------------------------------|
| Manufacturing material         | High resistance technopolymer |
| Treatment type                 | -                             |
| Surface finishing              | -                             |
| Color                          | -                             |
| Execution                      | -                             |
| Dimensions                     | -                             |
| Depth                          | -                             |
| Front-plate dimension          | -                             |
| Hole type                      | -                             |
| IP Protection degree           | -                             |
| Additional IPdegree protection | -                             |
| Resistance to Glow wire        | -                             |
| Flame rating according UL94    | -                             |
| Corrosivity category           | -                             |
| Net Weight                     | 0.03 KG                       |
| Working Environment Temp.      | Min: - ;Max: -                |
| Warehousing Temperature        | Min: - ;Max: -                |

#### Technical data switch

|                             |            |
|-----------------------------|------------|
| Thermal current             | -          |
| Rated short-circuit current | -          |
| Terminals type              | -          |
| Conductors section (Cu)     | Min: ;Max: |
| Terminal tightening torque  | -          |
| Auxiliary status contacts   | -          |
| Padlockable handle          | -          |
| Operating category          | -          |

#### Reference Standards and Directives

|                                  |                                                                                                           |
|----------------------------------|-----------------------------------------------------------------------------------------------------------|
| Certification and approval marks | UKCA, CE                                                                                                  |
| Directives                       | 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)                                                    |
| Reference Standards              | EN 60669-1/IS1:2009, EN 60669-1:1999, EN 60669-1:1999/A1:2002, EN 60669-1:1999/A2:2008, EN IEC 63000:2018 |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.