




SERIES CAM
CMP_INT
CODE 292623



Datasheet

Electrical characteristics

Rated current	200A
Supply Voltage	690V~ 50/60Hz
Poles	4P
Rated insulation voltage	690 V
Insulation Class	II
CAM layout	3
Function Apparatus Control	One way switches
Type of protection	None

Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	Blue RAL 5015 (Cover), RAL 7042 (Base)
Execution	Wall mounting
Dimensions	370X250X255 mm
Depth	-
Front-plate dimension	-
Hole type	Window type B
IP Protection degree	IP65
Additional IPdegree protection	-
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	7.07 KG
Working Environment Temp.	Min: -25°C ;Max: +60°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

Technical data switch

Thermal current	200 A
Rated short-circuit current	40,5 kA
Terminals type	M8X25
Conductors section (Cu)	Min: ;Max:
Terminal tightening torque	15-22 Nm
Auxiliary status contacts	Max 2 (optional)
Padlockable handle	2 locks Ø4,5 mm max

Operating category

a	Tensione	Corrente / Potenza
Rating	Voltage	Current / Power
AC-22A	230 V	200 A
	400 V	200 A
	500 V	200 A
	690 V	200 A
AC-23A	230 V	200 A
	400 V	200 A
	500 V	200 A
	690 V	200 A
AC-23A	230 V	60 kW
	400 V	110 kW
	500 V	132 kW
	690 V	200 kW

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)

Reference Standards EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-1:2007/A2:2014, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN 60947-3:2009/A2:2015, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.