



**SERIES CEE-Ex
PLUG**

CODE 477763EX



Datasheet

Specifications

Net Weight	152 G
Rated current	16A
Frequency	100-300Hz
IP Protection degree	IP66
Poles	2P+ $\perp$
Clock Position	10h
Rated operating voltage	>50V ●
Rated insulation voltage	500 V V
Manufacturing material	Technopolymer Recyclable Palazzoli
Execution	Mobile
Hole type	Pg13.5 polyamide
Standard plug-socket	IEC 60309-2

Reference Standards and Directives

Certification and approval marks EX, CE

Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/34/EU (ATEX), 2014/35/EU (LVD)
Reference Standards	EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-15:2010 , EN 60079-31:2014, EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309 -1:1999/A2:2012, EN 60309-2:1999, EN 60309-2:1999/A2:2012, EN IEC 63000:2018

Atex characteristics

ATEX application zone	Zones 2-22
Dust Atex execution (Tmax1)	II 3D - Ex tc IIIC T65 °C Dc
Gas Atex execution (Tmax1)	II 3G - Ex nA IIC T6 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.