




SERIES DRIVEBOX ENCLOSURE

CODE **158280**



Datasheet

Electrical characteristics

Insulation Class	II
Rated insulation voltage	690 V
Rated operating voltage	600-690V AC
Connecting Terminals	Pierce-through
Type of protection	-
Fuse Type	-

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/35/EU (LVD)

Reference Standards CEI 64-20:2023, EN 60670-1:2005, EN 60670-1:2005/A1:2013, EN 60670-1:2005/AC:2007, EN 60670-1:2005/AC:2010, EN 60670-22:2006, EN IEC 63000:2018

Mechanical characteristics

Manufacturing material	High resistance technopolymer
Treatment type	-
Surface finishing	-
Color	Blue RAL 5012 (Cover), RAL 7042 (Base)
Execution	Wall mounting
Hole type	-
Direct output	1xM25
IP Protection degree	IP66
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -25°C ;Max: +50°C
Warehousing Temperature	Min: -30°C ;Max: +70°C
Functional maintenance	-
Resistance to temperature	-
Line cable sections	2,5-50 mm²
Tightening diameter	8 ÷ 18,2 mm
Dimensions	245X165X130 mm
Net Weight	0.91 KG

The images are purely indicative. Palazzoli reserves the right to make changes without notice.