




SERIES CAM
CMP_INT
CODE 276803



40A - 63A



Datasheet

Electrical characteristics

Rated current	40A
Supply Voltage	500V~ 50/60Hz
Poles	4P
Rated insulation voltage	690 V
Insulation Class	-
CAM layout	3
Function Apparatus Control	One way switches
Type of protection	None

Mechanical characteristics

Manufacturing material	-
Treatment type	-
Surface finishing	-
Color	-
Execution	Blackplane
Dimensions	94X94X129 mm
Depth	92
Front-plate dimension	-
Hole type	-
IP Protection degree	IP00
Additional IPdegree protection	IP65 front plate
Shock resistance	-
Resistance to Glow wire	960°C (Switch)
Flame rating according UL94	V-0 (Switch)
Corrosivity category	-
Net Weight	0.66 KG
Working Environment Temp.	Min: -25°C ;Max: +60°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

Technical data switch

Thermal current	40 A
Rated short-circuit current	10 kA
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 4 mm ² ;Max: 10 mm ²
Terminal tightening torque	2 Nm
Auxiliary status contacts	-
Padlockable handle	-

Operating category

Categoria Rating	Tensione Voltage	Corrente / Potenza Current / Power
AC-22A	230 V	40 A
	400 V	40 A
	500 V	40 A
AC-23A	230 V	40 A
	400 V	40 A
	500 V	40 A
AC-23A	230 V	12.7 kW
	400 V	22.2 kW
	500 V	27.7 kW
AC-3	230 V	11.2 kW
	400 V	19.4 kW
	500 V	24.2 kW

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2014/35/EU (LVD)

Reference Standards EN 60947-1:2007, EN 60947-1:2007/A1:2011, EN 60947-1:2007/A2:2014, EN 60947-3:2009, EN 60947-3:2009/A1:2012, EN 60947-3:2009/A2:2015

The images are purely indicative. Palazzoli reserves the right to make changes without notice.