




SERIES CAM-SZ
CMP_INT
CODE 265632



Adattatore 63-100A
Fondoquadro



Datasheet

Electrical characteristics

Rated current	63A
Supply Voltage	690V~ 50/60Hz
Poles	2P
Rated insulation voltage	690 V
Insulation Class	-
CAM layout	1
Function Apparatus Control	One way switches
Type of protection	-

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Treatment type	-
Surface finishing	-
Color	-
Execution	Board
Dimensions	99X99X128 mm
Depth	93
Front-plate dimension	67x67
Hole type	-
IP Protection degree	-
Additional IPdegree protection	IP65 front plate
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	0.65 KG
Working Environment Temp.	Min: -25°C ;Max: +60°C
Warehousing Temperature	Min: -40°C ;Max: +80°C

Technical data switch

Thermal current	63 A
Rated short-circuit current	10 kA
Terminals type	Screw - indirect clamping
Conductors section (Cu)	Min: 10 mm ² ;Max: 35 mm ²
Terminal tightening torque	3 Nm
Auxiliary status contacts	-
Padlockable handle	2 locks Ø4 mm max

Operating category

Categoria Rating	Tensione Voltage	Corrente / Potenza Current / Power
AC-22A	230 V	63 A
	400 V	63 A
	500 V	63 A
	690 V	63 A
AC-23A	230 V	63 A / 20.1 kW
	400 V	63 A / 34.9 kW
	500 V	63 A / 43.6 kW
	690 V	63 A / 60.2 kW
AC-3	230 V	40 A / 12.7 kW
	400 V	40 A / 22.2 kW
	500 V	40 A / 27.7 kW
	690 V	40 A / 38.2 kW

Reference Standards and Directives

Certification and approval marks CE, UKCA, IMQ

Directives 2014/35/EU (LVD)

Reference Standards EN IEC 60947-1:2021, EN IEC 60947-1:2021/AC:2023-01, EN IEC 60947-3:2021, EN IEC 60947-3:2021/AC:2021-11

The images are purely indicative. Palazzoli reserves the right to make changes without notice.