



**SERIES domoTER
SWITCH**

CODE 630036



Datasheet

Electrical characteristics

Rated current	16A
Supply Voltage	250V 50/60Hz
Poles	1P+N
Insulation Class	II
CAM layout	-
Function Apparatus Control	One way switches
Type of protection	MCCB

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Color	
Execution	-
Dimensions	-
Depth	-
Hole type	-
IP Protection degree	IP55
Resistance to Glow wire	
Flame rating according UL94	
Net Weight	0.02 KG
Working Environment Temp.	Min: ;Max:
Warehousing Temperature	Min: ;Max:

Technical data switch

Thermal current	16 A
Rated short-circuit current	10 kA
Terminals type	-
Conductors section (Cu)	Min: ;Max:
Terminal tightening torque	-
Auxiliary status contacts	-
Padlockable handle	-
Operating category	

Reference Standards and Directives

Certification and approval marks	UKCA, CE
Directives	2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/30/EU (EMC), 2014/35/EU (LVD)
Reference Standards	EN 60898-1/A11:2005, EN 60898-1/A13:2012, EN 60898-1/AC:2004, EN 60898-1:2003, EN 60898-1:2003/A1:2004, EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.