

SERIES ENERGY BOX
DISTRIBUTION BOARD CONSTR.SITI
CODE 604101



Datasheet

Specifications

Net Weight	21 KG
	EBOX
power	7 kW
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
Resistance Glow Wire	650°C (Casing)
Shock resistance	IK10 according to IEC/EN 62262
Storage room temperature MAX	+70°C
Rated current	32A
Frequency	50/60Hz
IP Protection degree	IP65
Poles	4P
Rated operating voltage	230V
Manufacturing material	Technopolymer Recyclable Palazzoli
Socket Protection	With fuses
Execution	Portable
Outfit	WITH INSULATING CABINET
Insulation Class	II
Dimensions	680X585X340 mm
Hole type	M40
Interl. sock. 16A 2P+E 230V	4
Switch type	MCB 2P - 32A
No. of power outgoing	4
Differential protection	32A 2P 30mA
Emergency button	Yes

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.