

**SERIES B-SMART
TURRET**
CODE 576206



Datasheet

Specifications

Net Weight	23.34 KG
Rated current	63A
Frequency	50/60Hz
IP Protection degree	IP56
Poles	4P
Rated operating voltage	230-400V~
Manufacturing material	Stainless steel
Terminal type	35mmq - 6mmq (light)
Socket Protection	With magnetothermic
Outlet Sockets	4
Insulation Class	II
Dimensions	360X895X276 mm
Equipment	2 RUBINETTI
Hole type	M32
Interlocked sock.-outl. 16A 3P	1
Interlocked sock.-outl. 32A 3P	1
Interl. sock. 16A 2P+E 230V	2
Switch type	NESSUNO
Differential protection	16A 1+N 30MA 16A 3P 30MA 32A 4

Reference Standards and Directives

Certification and approval marks UKCA, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-3:2012, EN
61439-3:2012/AC:2019-04, EN 61439-7:2020,
EN IEC 63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.