




SERIES CONTACT  
TERMINAL BLOCK  
CODE 532725



| Codici | A<br>(mm) | B<br>(mm)             | C<br>(mm) | testa della vite che<br>sporge dalla morsetteria<br>(mm) |
|--------|-----------|-----------------------|-----------|----------------------------------------------------------|
| 532725 | 70        | 4,75                  | 19,5      | —                                                        |
| 532735 | 70        | 4,75                  | 24,5      | —                                                        |
| 532745 | 93        | 4,75 x 7 (foro ø4,75) | 28,2      | —                                                        |
| 532747 | 100       | 4,75                  | 25,2      | 28,2                                                     |
| 532748 | 175       | 4,75                  | 25,5      | —                                                        |
| 532755 | 70        | 4,75                  | 22,5      | —                                                        |
| 532765 | 93        | 4,75 x 7 (foro ø4,75) | 26,2      | —                                                        |
| 532768 | 175       | 4,75                  | 30        | —                                                        |



Datasheet

| Specifications                 |                               |
|--------------------------------|-------------------------------|
| Connecting Terminals           | Double side-by-side terminals |
| Manufacturing material         | Ceramic                       |
| Contact material               | Brass                         |
| Terminals type                 | Screw - direct tightening     |
| No. poles for section          | 4x6 mm²                       |
| Conductors section (Cu)        | Min: 1.5 ;Max: 6 mm²          |
| Terminal tightening torque     | 0,8 Nm                        |
| Rated current                  | 41A                           |
| Rated operating voltage        | 450V                          |
| Rated impul. withstand voltage | 6,000                         |
| Functional maintenance         | -                             |
| Working Environment Temp.      | Min: -50°C ;Max: +300°C       |
| Warehousing Temperature        | Min: -50°C ;Max: +100°C       |
| Net Weight                     | 0.07 KG                       |

| Reference Standards and Directives |                                                    |
|------------------------------------|----------------------------------------------------|
| Directives                         | 2011/65/EU (RoHS)2012/19/EU (WEEE)2014/35/EU (LVD) |
| Reference Standards                | EN 60999-1:2000EN IEC 63000:2018                   |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.