



**SERIES CEE**  
**PLUG**  
**CODE 476002**



## Datasheet

### Electrical characteristics

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| Rated current            | 16A                                               |
| Supply Voltage           | 24V 50/60Hz <span style="color: purple;">●</span> |
| Poles                    | 2P                                                |
| Clock Position           | -                                                 |
| Rated insulation voltage | 500 V                                             |
| Signal plug inserted     | -                                                 |

### Reference Standards and Directives

|                                  |                                                                                                                                                                                                  |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification and approval marks | UKCA, IMQ, CE                                                                                                                                                                                    |
| Directives                       | 2011/65/EU (RoHS), 2012/19/EU (WEEE),<br>Reg. EU 2023/988 (GPSR)                                                                                                                                 |
| Reference Standards              | EN 60309-1:1999, EN 60309-1:1999/A1:2007,<br>EN 60309-1:1999/A1AC:2014, EN 60309<br>-1:1999/A2:2012, EN 60309-2:1999, EN<br>60309-2:1999/A1:2007, EN 60309<br>-2:1999/A2:2012, EN IEC 63000:2018 |

### Mechanical characteristics

|                                |                                                 |
|--------------------------------|-------------------------------------------------|
| Manufacturing material         | High resistance technopolymer                   |
| Alveolus/plugs treatment       | -                                               |
| Color                          | Grey RAL 7042                                   |
| Tightening diameter            | 10,5÷23 mm                                      |
| Execution                      | Wall mounting                                   |
| IP Protection degree           | IP44                                            |
| Additional IPdegree protection | -                                               |
| Shock resistance               | IK08 according to IEC/EN 62262                  |
| Resistance to Glow wire        | 850°C                                           |
| Flame rating according UL94    | V-2                                             |
| Terminals type                 | Screw - direct tightening                       |
| Conductors section (Cu)        | Min: 4 mm <sup>2</sup> ;Max: 10 mm <sup>2</sup> |
| Terminal tightening torque     | 1,2 Nm                                          |
| Net Weight                     | 0.16 KG                                         |
| Working Environment Temp.      | Min: -25°C ;Max: +50°C                          |
| Warehousing Temperature        | Min: -30°C ;Max: +70°C                          |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.