

SERIES ENERGY
DISTRIBUTION METALBOX RD CONSTR.SITI
CODE 677102



Datasheet

Specifications

Net Weight	108 KG
	EBOX
power	78 kW
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
Shock resistance	IK10 according to IEC/EN 62262
Storage room temperature MAX	+70°C
Rated current	125A
Frequency	50/60Hz
IP Protection degree	IP65
Poles	4P
Rated operating voltage	400V ●
Manufacturing material	Technopolymer Recyclable Palazzoli
Socket Protection	With magnetothermic , MAGNETOTERMICO
Execution	Wall mounting or on support
Outfit	WITH METAL CABINET
Insulation Class	II
Dimensions	1530X1330X690 mm
Hole type	M50
Switch type	MCB 4P - 125A
No. of power outgoing	7
Differential protection	125A 4P 30mA
Direct output 2P 25A	2
Direct output 4P 32A	3

Reference Standards and Directives

Certification and approval marks CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.