



**SERIES domoTER**  
**SOCKET OUTLET**  
**CODE 630050**



## Datasheet

### Electrical characteristics

|                          |               |
|--------------------------|---------------|
| Rated current            | 10/16A        |
| Supply Voltage           | 250V~ 50/60Hz |
| Poles                    | 2P+ $\perp$   |
| Clock Position           | -             |
| Rated insulation voltage | -             |
| Signal plug inserted     | -             |

### Reference Standards and Directives

|                                  |                                                                                                                                                                           |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification and approval marks | CE                                                                                                                                                                        |
| Directives                       | 2011/65/EU (RoHS), 2012/19/EU (WEEE), Reg. EU 2023/988 (GPSR)                                                                                                             |
| Reference Standards              | CEI 23-50/V1:2008, CEI 23-50/V2:2011, CEI 23-50/V3:2015, CEI 23-50/V4:2015, CEI 23-50:2007, EN IEC 63000:2018, IEC 60884-1/A1:2006, IEC 60884-1/A2:2013, IEC 60884-1:2002 |

### Mechanical characteristics

|                                |                                      |
|--------------------------------|--------------------------------------|
| Manufacturing material         | Technopolymer Recyclable Palazzoli   |
| Alveolus/plugs treatment       | -                                    |
| Color                          | Grey RAL 7035                        |
| Tightening diameter            | -                                    |
| Execution                      | Panel mounting                       |
| IP Protection degree           | IP20                                 |
| Additional IPdegree protection | -                                    |
| Resistance to Glow wire        | 850°C (Live contact), 650°C (Casing) |
| Flame rating according UL94    | V-2 (Live contact), HB (Casing)      |
| Terminals type                 | Screw - indirect clamping            |
| Conductors section (Cu)        | Min: ;Max:                           |
| Terminal tightening torque     | 0,8 Nm                               |
| Net Weight                     | 0.03 KG                              |
| Working Environment Temp.      | Min: -15°C ;Max: +50°C               |
| Warehousing Temperature        | Min: -30°C ;Max: +70°C               |

The images are purely indicative. Palazzoli reserves the right to make changes without notice.