

**SERIES ENERGY BOX  
DISTRIBUTION BOARD CONSTR.SITI**

**CODE 606104**



## Datasheet

### Specifications

|                                |                                       |
|--------------------------------|---------------------------------------|
| Net Weight                     | 23 KG                                 |
|                                | EBOX                                  |
| power                          | 30 kW                                 |
| Storage room temperature MIN   | -30°C                                 |
| Max. Amb. Temp.                | +50°C                                 |
| Min. Amb. Temp.                | -25°C                                 |
| Resistance Glow Wire           | 650°C (Casing)                        |
| Shock resistance               | IK10 according to IEC/EN 62262        |
| Storage room temperature MAX   | +70°C                                 |
| Rated current                  | 63A                                   |
| Frequency                      | 50/60Hz                               |
| IP Protection degree           | IP65                                  |
| Poles                          | 4P                                    |
| Rated operating voltage        | 400V ●                                |
| Manufacturing material         | Technopolymer Recyclable<br>Palazzoli |
| Socket Protection              | With fuses                            |
| Execution                      | Portable                              |
| Outfit                         | WITH INSULATING CABINET               |
| Insulation Class               | II                                    |
| Dimensions                     | 680X585X340 mm                        |
| Hole type                      | M40                                   |
| Interlocked sock.-outl. 16A 3P | 2                                     |
| Interlocked sock.-outl. 32A 3P | 1                                     |
| Interl. sock. 16A 2P+E 230V    | 3                                     |
| Switch type                    | MCB 4P - 63A                          |
| Differential protection        | 63A 4P 30mA                           |

### Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),  
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC  
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.