



SERIES domoTER
CMP_CASS
CODE 630003



Datasheet

Electrical characteristics

Insulation Class	II
Rated insulation voltage	-
Rated operating voltage	-
Dissipable Power	-

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Treatment type	-
Surface finishing	-
Color	Grey RAL 7035
Execution	Wall mounting

Cover type	Blind
N. of modules on DIN rail	-
Hole type	-
Window type	-
IP Protection degree	IP40
Additional IPdegree protection	-

Resistance to Glow wire	850°C (Live contact), 650°C (Casing)
Flame rating according UL94	V-2 (Live contact), HB (Casing)
Corrosivity category	-
Working Environment Temp.	Min: -15°C ;Max: +50°C
Warehousing Temperature	Min: -30°C ;Max: +70°C
Dimensions	120X82X58 mm

Internal dimensions	-
Net Weight	0.11 KG

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2014/35/EU (LVD)

Reference Standards EN 60670-1:2005, EN 60670-1:2005/A1:2013, EN 60670-1:2005/AC:2007, EN 60670-1:2005/AC:2010

The images are purely indicative. Palazzoli reserves the right to make changes without notice.