




**SERIES ALARM-Ex
SIREN**
CODE 900453EX



Datasheet

Specifications

Net Weight	1.25 KG
Rated current	1,4A
Frequency	50/60Hz
IP Protection degree	IP66
Poles	2P+ $\frac{1}{2}$
Rated operating voltage	24V
Manufacturing material	Aluminum alloy
power	33,8 VA
Hole type	M20
Sound level at 1 mt.	104/102dB dB
Acoustic Signal Type	D - continuous sound according to manual control
Operational working temp	-40 T 40 °C

Reference Standards and Directives

Certification and approval marks EX, NYCE COLOMBIA, CE, IECEx

Directives 2011/65/EU (RoHS), 2014/30/EU (EMC), 2014/34/EU (ATEX)

Reference Standards EN 60079-31:2014, EN 60079-7:2015, EN 60079-7:2015/A1:2018, EN 62080:2009/A2:2015, EN 62080:2009, EN 60079-0:2018, EN IEC 63000:2018

Atex characteristics

ATEX application zone	Zones 1-2-21-22
Dust Atex execution (Tmax1)	II 2D - Ex tb IIIC T85/T90°C Db
Gas Atex execution (Tmax1)	II 2G - Ex eb IIC T3 Gb

The images are purely indicative. Palazzoli reserves the right to make changes without notice.