




SERIES TAIS CUBE
EMPTY DISTRIBUTION BOARD
CODE 550002



MISURA	A	B	C
1	258	304	160
2	340	430	180
3	449	506	220
4	449	656	220
5	558	656	260
6	631	807	300
7	848	1058	350



Datasheet

Electrical characteristics

Insulation Class	II
Rated insulation voltage	1000 Vac - 1500 Vdc
Dissipable Power	90W

Reference Standards and Directives

Certification and approval marks UKCA, NYCE COLOMBIA, CE

Directives 2014/35/EU (LVD)

Reference Standards EN 62208:2011

Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Color	Grey RAL 7035
Execution	Wall mounting
Door type	BLIND
Number and type of closures	2 triangle key closure
N. of modules on DIN rail	-
Internal working depth	120
IP Protection degree	IP66
Shock resistance	IK10 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -30 °C ;Max: +90 °C
Warehousing Temperature	Min: -50 °C ;Max: +90 °C
Dimensions	340X430X180 mm (WHD)
Internal dimensions	280X375X120 mm
Net Weight	4.29 KG
Maximum permissible load	On the doors: 10 kg; Mounting surfaces: 20 kg; On the bottom: 20 kg

The images are purely indicative. Palazzoli reserves the right to make changes without notice.