

SERIES ENERGY GO
DISTRIBUTION BOARD CONSTR.SITI
CODE 670061



Datasheet

Specifications

Net Weight	9 KG
	ASC1
Shock resistance	IK08 according to IEC/EN 62262
Storage room temperature MIN	-30°C
Max. Amb. Temp.	+50°C
Min. Amb. Temp.	-25°C
UL94 Flamability	V-2 (Live contacts holder)
Resistance Glow Wire	650°C (Body of the socket) , 850°C (Live contacts holder)
Storage room temperature MAX	+70°C
Rated current	32A
Frequency	50/60Hz
IP Protection degree	IP66
Poles	4P
Rated operating voltage	230-400V~
Manufacturing material	Technopolymer Recyclable Palazzoli
Socket Protection	MAGNETOTERMICO E DIFFERENZIALE
Execution	Portable
Outlet Sockets	6
Outfit	WITHOUT PLATE
Insulation Class	II
Dimensions	350X456X160 mm
Industr. sock.-out. 16A 2P+E 2	3
Industr. sock.-outl. 16A 3P+E	3
Plug type	3P+N+T - 32A

Reference Standards and Directives

Certification and approval marks CE, UKCA

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE),
2014/30/EU (EMC), 2014/35/EU (LVD)

Reference Standards EN 61439-1:2011, EN 61439-4:2013, EN IEC
63000:2018

The images are purely indicative. Palazzoli reserves the right to make changes without notice.