

【Model No.】	CP-2FABSJ
--------------------	-----------

【Electrical Data】		
Effective Electrical Travel	90 ±3	°
Total Resistance	1	kΩ
Total Resistance Tolerance	±20	%
Independent Linearity	±3	%
Max. Input Voltage	DC18/50°C	W
Insulation Resistance	MIN. 100/DC1000V	MΩ
Dielectric Strength	AC1000/1min.	V
Temperature Coefficient Of Resistance	±400	ppm/K

【Mechanical Data】		
Gear Ratio	100 ±5	
Torque	20~100	mN·m
Repeatability	MIN. 1	N·m
Thrust Load Tolerance	3	N
Radial Load Tolerance	4	N
Mass	35 Appx.	g

【Environmental Data】		
Life	5 Million	cycle
Category Temperature Range	-40~+100	°C
Storage Temperature Range	-40~+100	°C
Vibration	245m/s ² 20~500Hz 3axis 2hours each	
Shock	500m/s ² 11ms 3axis 6axis 3times	
IP Rating	IP65	

■ Handling Instruction

To avoid burnout of resistive element, do not supply 1mA Min. current to terminal 2.

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Office North America:

Angst+Pfister North America Inc.
10391 Brecksville Rd.
US-Brecksville, OH 44141
Phone +1 440 375-5212
info.apus@angst-pfister.com

Scan here and get an overview of personal contacts!



<https://sensorsandpower.angst-pfister.com/en/>
