



Selection Guide of CP-2FL




Contact type potentiometer using Conductive Plastic Element

Subject		Specifications
Basic Characteristics	Dimension/Mass	Φ22.3×12.5mm / 20g approx.
	Effective Electrical Travel	340°
	Independent Linearity	±1% (Option ±0.5%)
	Total Resistance (Input voltage)	1kΩ (18Vmax.), 5kΩ (40Vmax.), 10kΩ (56Vmax.)
	Total Mechanical Travel	360° Endless
	Output	Voltage ratio
Electrical	Output Range	Voltage ratio 0~100%
	Resolution	Infinitesimal
	Rated Dissipation	0.5W / 50°C
	Temp. Coefficient of Resistance	±400ppm / K
Environmental	Life	MIN. 10 Million Revolution
	Category Temperature Range	-40~100°C
	Vibration	150m/s ² 2000Hz 3 axes 2 hours each
	Shock	500m/s ² 11ms 3 times each in 6 directions


Model Number Designation

CP-2FL	-	6	1 K	0.5%
Series Number		Shaft dia.	Total Resistance	Independent Linearity
		None = Φ3.175mm 6 = Φ 6 mm	1,5,10KΩ	None : ±1% ±0.5% : ±0.5%


■ Output Characteristics



■ Schematic



■ Dimension



We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Office North America:

Angst+Pfister North America Inc.
10391 Brecksville Rd.
US-Brecksville, OH 44141
Phone +1 440 375-5212
info.apus@angst-pfister.com

Scan here and get an overview of personal contacts!



<https://sensorsandpower.angst-pfister.com/en/>
