

Product Specification of:

O₂ - **leadfree** Medical Sensor / Type MLF - 16DE

:: KEY FEATURES ::

Lead free, RoHS compliant, long-life expectancy, digital sensor output signal, EEPROM and temperature sensor on PCB.

All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa and gas flow > 2.5 L/min.

Measurement Range:	0.01 to 100 Vol.%O ₂
Resolution:	15 Bit used (16 Bit processor, 1 Bit for algebraic sign)
Output signal	0 to 32768 Digits (gain amplifier 1)
Initial Output Signal Range:	2546 to 4455 Digits @ dry ambient air
Electrical connector	4-pin Molex (digital sensor output signal, I ² C interface)
Power Consumption:	< 15 mW @ dry ambient air
Mechanical Mating Connector:	fits for M16x1 DIN 13 or 5/8-24 UNEF
Nominal Sensor Life:	> 2,000,000 Vol.%O ₂ h
Expected Operating Life:	4 years @ ambient air, depending on application
Response Time t₉₀:	< 7 s
Signal Drift (long term):	< 0.1%/month of sensor output signal @ dry ambient air
Signal Drift (short term):	< 0.1 Vol.%O ₂ / day @ dry ambient air, constant environmental / measurement conditions
Static Temperature Error:	< ±10% @ 40-50 °C; < ±1.5% @ 20-40 °C < ±2% @ 10-20 °C; < ±10% @ 0-10 °C
Operating Temperature:	0 - 40 °C; intermittent 40 - 50 °C
Ambient Pressure Range:	500 to 1250 mbar
Zero Offset Equivalents:	< 0.3 Vol.%O ₂ @ 100 Vol.%N ₂ applied for 5 min
Linearity Error:	< 3 % @ 100 Vol.%O ₂ applied for 5 min
Influence of Humidity:	- 0.03 % rel. O ₂ reading per % RH
Temperature Compensation:	NTC on sensor PCB (read out of sensor signal is already temperature compensated, no separate temperature compensation necessary)
Interferences:	according to DIN EN ISO 80601-2-55
Weight:	approximately 20g
Material in contact with media:	PPS, PTFE, ABS, FPM, stainless steel



:: STORAGE CONDITIONS IN UNOPENED ORIGINAL PACKAGE ::

Temperature Range:	- 20 °C to 40 °C 5 °C to 25 °C recommended 40 °C to 50 °C maximum 1 week
Ambient Pressure Range:	500 to 1250 mbar
Humidity:	up to 100% RH, non condensing
Shelf Life:	< 6 months recommended

:: RELATED PRODUCTS ::

Product	Part-No.	Housing Colour	Other Specifics
O2-Sensor MLF-16	47 03 16	white	RoHS compliant, lead free, analog sensor output signal
O2-Sensor MLF-16D	47 11 16	white	RoHS compliant, lead free, digital sensor output signal
O2-Sensor MLF-16DE	47 14 16	white	RoHS compliant, lead free, digital sensor output signal, EEPROM and temperature sensor on PCB

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Office North America:

Angst+Pfister North America Inc.
10391 Brecksville Rd.
US-Brecksville, OH 44141
Phone +1 440 375-5212
info.apus@angst-pfister.com

Scan here and get an overview of personal contacts!



<https://sensorsandpower.angst-pfister.com/en/>
