



THIS PRODUCT COMPLIES WITH RoHS DIRECTIVE.



SPECIFICATIONS

ELECTRICAL STROKE	: 150±1mm
TOTAL RESISTANCE	: 1・2・5・10kΩ ±20%
INDEPENDENT LINEARITY	: ±0.3% (AVAILABLE: ±0.1%)
POWER RATING	: 3W/70℃
OUTPUT SMOOTHNESS	: 0.1% MAX.
INSULATION RESISTANCE	: 100MΩ MIN. DC500V
DIELECTRIC STRENGTH	: AC500V 1MINUTE
TEMPERATURE COEFFICIENT OF RESISTANCE	: ±400ppm/K
TOTAL MECHANICAL STROKE	: 153±2mm
FRICTION	: 2N MAX.

SCHEMATIC



・ 1, 2, 3, 4: CONNECTOR PIN No.

NAME PLATE

Model: LP-150F-13
No. 123456004-RES.1kΩ
MIDORI PRECISIONS TOKYO

REV	DATE	DESCRIPTION	DRAWN	CHKD

DRAWING FOR APPROVAL			SPEC. NO.	
MODEL: LP-150F-13				
APPROVED	TOLERANCE	DATE	MIDORI PRECISIONS CO., LTD.	
CHECKED <i>M. Kamiki</i>	±10 ±0.25	1.27.'10	DRAWING NO.	
DRAWN <i>K. Yoshino</i>	10 < ±100 ±0.5	SCALE 1:1	B-MPE-B95	
	100 < ±1.0	DRAWING PRACTICE		
	ANGLE ±1.5°			

We are here for you. Addresses and Contacts.

Headquarter Switzerland:

Angst+Pfister Sensors and Power AG
Thurgauerstrasse 66
CH-8050 Zurich

Phone +41 44 877 35 00
sensorsandpower@angst-pfister.com

Office Germany:

Angst+Pfister Sensors and Power Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim

Phone +49 89 374 288 87 00
sensorsandpower.de@angst-pfister.com

Office North America:

Angst+Pfister North America Inc.
10391 Brecksville Rd.
Brecksville, OH 44141

Phone +1 440 375-5212
info.apus@angst-pfister.com

Scan here and get an overview of personal contacts

