



Image may differ from product. See technical specification for details.

TLMR 201

Electro-mechanical single point lubricant dispenser, 12-24V DC powered

With a relatively high dispensing pressure, SKF TLMR can operate at long distances and provide optimum results with difficult-to-reach and unsafe lubrication points. Its robust design makes them suitable for operating in a wide temperature range in presence of vibrations. Powered by batteries or 12-24 V DC by plug M12-A (not included) and delivered with or without grease.

- Flexible temperature independent dispense rate from 1 to 24 months
- Available cartridges of 120 and 380 ml of SKF grease
- Maximum discharge pressure of 30 bars (435 psi) during the dispensing period

- Wide temperature range, especially suitable for engine rooms, and hot fan applications, as well as wind turbine applications.

Overview

Performance

Highest dispense setting 120 ml cartridge	3.9 ml/d
Highest dispense setting 380 ml cartridge	12.5 ml/d
Lowest dispense setting 120 ml cartridge	0.16 ml/d
Lowest dispense setting 380 ml cartridge	0.5 ml/d
Maximum pressure	30 bar

Properties

Ambient temperature range	-25.0 – 70.0 °C
Battery	none
Connecting thread	G 1/4
Degree of protection (IP)	DIN EN 60529: IP 67 DIN 40 050-9: IP 6k9k
Drive mechanism	Electro mechanical
LED indicator	Green LED (every 8 sec): OK Green and red LED (every 8 sec): Almost empty Red LED (every 8 sec): Error
Maximum feed line length	5 m
Nominal emptying time	User adjustable: 1, 2, 3, 6, 9, 12, 18 and 24 months or purge
Nominal emptying time	1.0 – 24.0 mo
Power source	12-24 V DC via M12-A connection
Purge setting	31 ml

Logistics

Product net weight	0.9 kg
UNSPSC code	15121902
eClass code	23-06-10-14

Compatible products

Accessory

Angle connection 45 degrees	LAPA 45
Angle connection 90 degrees	LAPA 90
Extension 35 mm	LAPE 35

Extension 50 mm	LAPE 50
Tube connector, male G 1/4 for 6 mm tube	LAPF M1/4S
Tube connector, male 1/4 for 8 mm tube	LAPF M1/4SW
Tube connector, male G 1/8 for 6 mm tube	LAPF M1/8S
Grease nipple with male thread G1/4	LAPG 1/4
Y connection, with male threads G1/4 to female G1/4	LAPM 2
Nipple with thread female G1/4 to male G1/2	LAPN 1/2
Nipple with thread female G1/4 to male G1/4	LAPN 1/4
Nipple with threads female G 1/4 to male 1/4 -28 UNF	LAPN 1/4UNF
Nipple with threads female G 1/4 to male G1/8	LAPN 1/8
Nipple with threads female G 1/4 to male M10x1.5	LAPN 10
Nipple with threads female G 1/4 to male M12	LAPN 12
Nipple with threads female G 1/4 to male G 3/8	LAPN 3/8
Nipple with threads female G 1/4 to male M6	LAPN 6
Nipple with threads female G 1/4 to male M8x1.25	LAPN 8
Flexible tube, 1000 mm long, 6 x 4 mm	LAPT 1000S
Extra strong flexible tube, 1000 mm long, 8 x 6 mm	LAPT 1000SW
Flexible tube, 5000 mm long, 6 x 4 mm	LAPT 5000S
Extra strong flexible tube, 5000 mm long, 8 x 6 mm	LAPT 5000SW
Non return valve G1/4	LAPV 1/4
Non return valve G1/8	LAPV 1/8

Spare part

Spare battery lid kit for Automatic lubricant dispenser	TLMR 1-2
Spare bracket kit for Automatic lubricant dispenser	TLMR 1-3
Spare closure plug kit for Automatic lubricant dispenser	TLMR 1-4

Spare sealing ring for Automatic lubricant dispenser	TLMR 1-5
Spare battery holder for Automatic lubricant dispenser	TLMR 1-6

Recommended product

Refill cartridge containing high loads and extreme pressure bearing grease, 380 ml, without battery for Electro-mechanical cabled single point lubricant dispenser	LGEP 2/MR380
Refill cartridge containing high loads, slow rotations and severe vibrations bearing grease, 380 ml, without battery for Electro-mechanical cabled single point lubricant dispenser	LGEV 2/MR380
SKF TLMR refill set with SKF LGFP 2	LGFP 2/MR380
Refill cartridge containing high load, high temperature, high viscosity bearing grease, 380 ml, without battery for electro-mechanical single point lubricant dispenser	LGHB 2/MR380
Refill cartridge containing rust inhibiting bearing grease, 380 ml, without battery for Electro-mechanical single point lubricant dispenser	LGMT 3/MR380
Refill cartridge containing rust inhibiting bearing grease, 380 ml, with battery for Electro-mechanical single point lubricant dispenser	LGMT 3/MR380B
Refill cartridge containing high load, extreme pressure, wide temperature range bearing grease, 120 ml, without battery for Electro-mechanical single point lubricant dispenser	LGWA 2/MR120
Refill cartridge containing high load, extreme pressure, wide temperature range bearing grease, 380 ml, without battery for Electro-mechanical single point lubricant dispenser	LGWA 2/MR380
Refill cartridge containing high load, water and temperature fluctuation resistant grease, 380 ml, without battery for Electro-mechanical single point lubricant dispenser	LGWM 2/MR380

Component

Accessory cable plug M12x1, type M12-A for Automatic lubricant dispenser	TLMR 201-1
--	----------------------------

Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) (556007-3495 · Gothenburg) ("SKF"), you agree to the following terms and conditions:

Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

Third Party Services

When viewing YouTube content via the SKF website(s) (i.e. using [YouTube API Services](#)), you agree to be bound by the [YouTube Terms of Service](#).

Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

Changes

SKF reserves the right to make changes or additions to this website / app at any time.